

ARIZONA COURTLINES, INC. SPECIFICATIONS
1D-SFFB (ACI MODEL #)
SINGLE MAST - SIDE FOLD - FRONT BRACED

STEM / MAIN MAST

Vertical mast shall consist of 6 5/8" O.D. schedule 20 structural steel tubing, with one welded diagonal front brace constructed of 1 1/2" x 3" heavy wall square tubing. A heavy-duty 2" x 4" structural steel channel shall be used for the top support. This all welded design provides maximum strength and durability.

BACKBOARD / GOAL SUPPORT

The upper bank extension shall be all-welded to prevent movement and locks in backboard dimension at 6" to comply with official NCAA and NFSA regulations. The lower goal to mast bracket eliminates the strain on the backboard.

STEM HANGER

The stem hanger shall be fully adjustable to allow precise frame placement and leveling of the main mast. The stem hanger shall also attach to the overhead support with (2) clamps per hanger. The stem hangers shall be offset to allow the counter weight to lock the backstop in playing position.

SIDE BRACING

Side brace shall position backstop plumb and in the precise location. Side brace consist of 2" tubing which folds to the side with an adjustable jackknife assembly when backstop is stored in the horizontal position. Jackknife shall unlock by upward force of hoist cable.

OVERHEAD SUPPORT

3 1/2" tubing shall be used for truss spacing which does not exceed 13'-0". For truss spacing which exceeding 13'-0", 6 5/8" tubing shall be used. Pipes shall be furnished with end caps.

NUTS AND BOLTS

All bolts shall be a minimum 1/2" diameter. All 1/2"diameter bolts shall have a pull out strength of no less then 17,000 lbs. and shall have a shearing strength of no less then 12,100 lbs. All nuts and bolts shall be zinc plated.

BACKSTOP / PARTS FINISH

Backstop and all parts shall be painted one coat black paint. Other colors are available.