

ARIZONA COURLINES, INC.
WP-CP- (WALL PADDING)
CORNER PADDING

VINYL COVER

Vinyl cover shall be 14oz per square yd. vinyl coated polyester with 1000-denier polyester base fabric. Vinyl shall be wrapped a minimum of 2" around backside of wood and shall be stapled every 3" with finish staples. Material shall be bacteria resistant and shall meet National Fire Protection Standard 701. Vinyl cover color to be selected from ACI's standard colors. Cover material shall meet the California State Fire Marshal minimum requirements.

FOAM

Polyurethane shall be manufactured from 2" open cell foam. Foam density shall range from 1.5 to 6 pounds per cubic foot. The open cell foam shall be capable of resisting heat of 158 degrees for 22 hours. Foam shall have a compression set of 90 percent. When tested in accordance with ASTM D-3574-86, foam shall have a minimum tear resistance of 1.2 pounds per linear inch, a minimum tensile strength of 12 - 18 psi, and a minimum elongation of 80% (Range: 80 - 150). Passes flammability specifications for Cal. 117, FMVSS 302, & NFPA 260.

WOOD BACKING

The wood backing shall be 3/8" plywood.

WP-CP-6	6'-0" Height
WP-CP-7	7'-0" Height
WP-CP-8	8'-0" Height
