

**ARIZONA COURTLINES, INC. (ACI)**  
**FB-SCG-3H - FOOTBALL/SOCCER GOAL COMBINATION SYSTEM (H-FRAME)**

- A. Uprights, 3-1/2" outside diameter steel (A53) pipe.
- B. Uprights extend 20'-0" above playing field surface.
- C. Uprights spacing: 24'-0" inside to inside (soccer standard).
- D. Crossbar assembly (ladder design), 3-1/2" outside diameter steel (A53) pipe.
- E. Crossbar's upper edge (football) 10'-0" above playing field surface.
- F. Crossbar's lower edge (soccer) 8'-0" above playing field surface.
- G. 1/4" thick formed steel (A36) adjustable support bracket (crossbar to upright).
- H. Top of uprights equipped with welded steel caps.
- I. 1/2" diameter grade 8 zinc plated hardware (adjustable support bracket).
- J. All hardware zinc plated.
- K. Galvanized finish on all pipes and brackets.
- L. Paint by others after installation if required.
- M. Powder coat finish available (additional cost).
- N. Footing: 1'-6" diameter x 3'-6" deep. Post 3'-0" into footing.
- O. Steel anchor pin welded to bottom of uprights to prevent removal and twisting.
- P. One year parts warranty.