

ARIZONA COURTLINES, INC. (ACI)

- **FBGP-54 - FOOTBALL GOAL POST (5-9/16" DIA. POST, 4'-0" EXTENSION)**
- **FBGP-55 - FOOTBALL GOAL POST (5-9/16" DIA. POST, 5'-0" EXTENSION)**
- **FBGP-56 - FOOTBALL GOAL POST (5-9/16" DIA. POST, 6'-0" EXTENSION)**

- A. Support post, 5-9/16" outside diameter steel (A53) pipe.
- B. Formed gooseneck support post. Vertical section outside of end zone for safety.
- C. Crossbar, 3-1/2" outside diameter steel (A53) pipe.
- D. Crossbar's upper edge 10'-0" above playing field surface.
- E. Uprights, 2" outside diameter steel (A53) pipe.
- F. Uprights spacing: 23'-4" inside to inside.
- G. Uprights extend 30'-0" above playing field surface.
- H. Heavy-duty adjustable sleeves located on crossbar ends for upright leveling.
- I. Welded steel caps on crossbar and upright ends.
- J. 1/2" diameter grade 8 zinc plated hardware for crossbar and upright positioning.
- K. 3/8" diameter grade 5 zinc plated self-threading bolts at all connections.
- L. Installer to drill for 3/8" self-threading bolts.
- M. All hardware zinc plated.
- N. All pipe galvanized finish.
- O. Paint by others after installation if required.
- P. Powder coat finish available (additional cost).
- Q. Footing: 3'-0" diameter x 4'-0" deep. Post 3'-6" into footing.
- R. Steel anchor pin welded to bottom of support post to prevent removal and twisting.
- S. One year parts warranty.