

ARIZONA COURTLINES, INC.
MODEL NO. VBP-S1
VOLLEYBALL POST - 3-1/2" STANDARD STEEL

Model No.	Description
<input type="checkbox"/> VBP-S1SP	Volleyball post, 3-1/2" standard steel, sleeve type, powder coat finish
<input type="checkbox"/> VBP-S1SPC	Center post, 3-1/2" standard steel, sleeve type, powder coat finish
<input type="checkbox"/> VBP-S1PP	Volleyball post, 3-1/2" standard steel, permanent, powder coat finish
<input type="checkbox"/> VBP-S1PPC	Center post, 3-1/2" standard steel, permanent, powder coat finish
<input type="checkbox"/> VBP-S1SG	Volleyball post, 3-1/2" standard steel, sleeve type, galvanized finish
<input type="checkbox"/> VBP-S1SGC	Center post, 3-1/2" standard steel, sleeve type, galvanized finish
<input type="checkbox"/> VBP-S1PG	Volleyball post, 3-1/2" standard steel, permanent, galvanized finish
<input type="checkbox"/> VBP-S1PGC	Center post, 3-1/2" standard steel, permanent, galvanized finish

- A. Meets requirements of FIVB (Federation of International Volleyball).
- B. Meets requirements of USAV (USA Volleyball).
- C. Meets requirements of AVP (Association of Volleyball Professionals).
- D. Meets requirements of NFHS (National Federation of State H.S. Association).
- E. 3-1/2" outside diameter steel (A53) post.
- F. Net height range: 4'-8" to 8'-1-1/2".
- G. Steel (A500) case net tension winch with bronze and steel worm gear set.
- H. Winch includes: bushings, cable drum, nylon belt, spring link and crank handle.
- I. Double hook steel (A53) post collars (2H) for lower net attachments.
- J. Double looped steel (A53) upper post collars (2L) for pulley attachment.
- K. T-handle equipped post collars and winch for quick height adjustments.
- L. Tackle pulley for cable routing to winch and post collar (2H).
- M. Tackle pulley incorporates clevis pin and hairpin cotter for easy pulley removal.
- N. Quick links (zinc plated) for tackle pulley attachment to post collar (2L).
- O. Black plastic pipe cap for top of powder coated posts.
- P. Galvanized pipe cap for top of galvanized posts.
- Q. Height adjustable rubber foot for sleeve type models.
- R. Welded anchor pin (1/2") eliminates pull out and twist on permanent models.
- S. One year parts warranty.