

**ARIZONA COURTLINES, INC.**  
**MODEL NO. BAD-238**  
**BADMINTON POST (STEEL) INDOOR / OUTDOOR**

- A. Post: 2-3/8" outside diameter schedule 40 steel pipe.
  - B. Each post equipped with grooved pipe cap to route net rope over top of post.
  - C. One post equipped with rope cleat to hold net tension.
  - D. Opposite post equipped with 3/8" eyebolt.
  - E. Bottom net ropes wrap around post to hold net tension.
  - F. Center of net shall be 5'-0" above the playing surface.
  - G. Posts available with galvanized or powder coat finish (specify).
  - H. All hardware is zinc plated.
  - I. One year parts warranty.
- 

**SPECIFY POST TYPE:**

- Indoor Floor Sleeve (w/ Coverplate):**  
Post shall be designed and fabricated for use with ACI model # FS-238.  
*See drawing (2-3/8" Details) and specification for FS-238 details.*
  - Outdoor Floor Sleeve (No Coverplate):**  
Post shall be designed and fabricated to allow for use with ACI model # FS-238-O.  
*See drawing (2-3/8" Details) and specification for FS-238-O details.*
  - Outdoor Floor Sleeve (w/ Coverplate):**  
Post shall be designed and fabricated to allow for use with ACI model # FS-238-OC.  
*See drawing (2-3/8" Details) and specification for FS-238-OC details.*
  - Permanent Post:**  
Post shall be fabricated for permanent in ground installation.  
*See drawing (2-3/8" Details) and specification for PERM-238 details.*
- 

**MODEL NO. BM-NET**  
**BADMINTON NET**

- J. Net shall be 20'-0" in length and 30" in height.
- K. The top, bottom, and each end binding shall be vinyl wrapped.
- L. Upper and lower ropes shall be 25'-0" in length (for use with posts 22'-0" on center).