

## ARIZONA COURTLINES, INC. SPECIFICATIONS

### **B A D - 3 1 2 (ACI MODEL #) BADMINTON POST (STEEL) INDOOR / OUTDOOR**

#### **POSTS**

Badminton posts shall be 3-1/2" diameter steel tubing. Posts shall extend 5'-3-1/2" above the playing surface. Top of post shall be equipped with a pipe cap to prevent water damage and improve appearance. One 3/8" diameter eyebolt shall be attached to each post 5'-1" above the playing surface. One post shall be equipped with a rope cleat to allow the user to pull the net tight and wind the rope around the cleat to hold net tension. The bottom net ropes shall be capable of wrapping around the post and being tied to hold net tension. Center of net shall be 5'-0" above the playing surface. Posts available with galvanized or powder coat finish (specify). All hardware is zinc plated.

#### **SPECIFY POST TYPE:**

- **Indoor Floor Sleeve (w/ Coverplate):**  
Post shall be designed and fabricated for use with ACI model # FS-312.  
*See drawing (3-1/2" Details) and specification for FS-312 details.*
- **Outdoor Floor Sleeve (No Coverplate):**  
Post shall be designed and fabricated to allow for use with ACI model # FS-312-O.  
*See drawing (3-1/2" Details) and specification for FS-312-O details.*
- **Outdoor Floor Sleeve (w/ Coverplate):**  
Post shall be designed and fabricated to allow for use with ACI model # FS-312-OC.  
*See drawing (3-1/2" Details) and specification for FS-312-OC details.*
- **Permanent Post:**  
Post shall be fabricated for permanent in ground installation.  
*See drawing (3-1/2" Details) and specification for PERM-312 details.*

---

### **B M - N E T (ACI MODEL #) BADMINTON NET**

Net shall be 20'-0" in length and 30" in height. The top, bottom, and each end binding shall be vinyl wrapped. Upper and lower ropes shall be 25'-0" in length. Net for use with posts 22'-0" on center. Custom nets available at additional cost (specify).